

Approved For Release 2002/10/09 : CIA-RDP66B00664R000400100073-6

DATE 1039Z 12 MAR 64

SECRET

ROUTING

2	9
3	10
4	11
5	12
6	13
7	14
8	15
	16

TO : DIRECTOR

FROM : [REDACTED] 25X1A

ACTION:

INFO : OPS 1-12

ROUTINE

25X1A

TOR 1254Z 12 MAR 64

25X1A

IN-67327

TO

INFO

CITE

LOGS

25X1A

25X1A

A. 5024A

B. 342

C. 12 MAR FOR 6 PLUS 35

D. HDQ DIR [REDACTED] 3, 5, 8, 26, 30, 33 25X1A

E. 1. MACH SENSOR HAS PITCH OSCILLATION OF PLUS AND MINUS 2 KTS AND PLUS AND MINUS 200FT WHEN AT 630 DEGREES AT PLUS 18.
2. BATTERY DISCHARGE LITE STAYS ON, FLICKERING, WHEN BELOW 75 PERCENT AND ALL ELECTRIC LOADS OFF. 3. Q-BAY PRESSURE LOST AT 4 PLUS 00 AFTER T.O. GOING UP TO PLUS 2 BY SIX HRS OF FLT. 4. AFTER Q-BAY PRESSURE WAS LOST HATCH HTR LITE GOES OFF INTERMITTENTLEY ACCOMPANIED BY RADIO NOISE EST FLUTTER, LOADMETER FLUTTER, AND BATTERY DISCHARGE LITE. ALL OK WITH HATCH HTR OFF.

F. AND G NEG.

END OF MESSAGE

GROUP 1
Excluded from automatic
downgrading and
declassification

Approved For Release 2002/10/09 : CIA-RDP66B00664R000400100073-6

REPRODUCTION BY OTHER THAN THE ISSUING OFFICE IS PROHIBITED. Copy No.